

## fitting instruction for the Pluvialis rainwater filter

### Requirement and needful tools:

The Pluvialis rainwater filter can be installed at any place of the downpipe if the place is vertical for a length of about 90cm (35 inch). For XXL models 130cm (51 inch)

A saw to saw off the downpipe  
A knife or a file or flintpaper for deburring the end sawed off.  
Screwdriver  
Some soap or washing liquid to moisten the rubber seal

### So you proceed the installation:

Choose a vertical place with a length of about 90cm (35 inch). For XXL models 130cm (51 inch).

Saw off the downpipe to a length of about 90cm (35 inch). For XXL models 130cm (51 inch)

Deburr the ends of the downpipe.

Take a rubber plumbing coupling (Component of the delivery, including stainless steel end clamps) and pull it on at the lower pipe of the downpipe. More easy if the rubber plumbing coupling is moistened with some soap or washing liquid.

Take the second rubber plumbing coupling (Component of the delivery, including stainless steel end clamps) and pull it on the upper part of the Pluvialis rainwater filter. More easy if the rubber plumbing coupling is moistened with some soap or washing liquid.

Put the rainwater filter between the downpipe. Now blame up the the rubber plumbing coupling and fix the stainless steel end clamps.

And the filter is already put together ready.

## Cleaning instructions for the Pluvialis rainwaterfilter

You clean your PLUVIALIS rain water filter as follows.

Loosen the screws of the rubber plumbing coupling. Push down the rubber plumbing coupling that you can take of the rain water filter.

Pull out the filter pad out of the case

Wash the filter with a sharp jet of water. It works with a garden tube in the garden best.

Aim the jet of water of the outside at the filter. Suit the filter to below meanwhile so that the water can flow off.

Point the jet of water also into the inside of the filter. Suit the filter to below meanwhile so that the rough dirt can fall out of the integrated space.

Cleaning doesn't need to be longer than carried out for 1 -3 minutes. The filter pad is then clean.

Put the filter pad into its case again.

Put the Pluvialis rainwater filter between the open ends of the downpipe again. Now blame up the the rubber plumbing coupling and fix the stainless steel end clamps.

Tip: Reinigen Sie Ihren PLUVIALIS Regenwasserfilter auf Ihrem Rasen oder Beet wenn diese sehr trocken sind. Dann haben Sie nicht nur Ihren Filter gereinig, sondern auch Ihren Garten bewässert.

Tip: You clean your rain water filter if your lawn is very dry. You then have cleaned your filter and also irrigated your garden.

